| "PVC" NSSK G.P. BILASPUR at KALOL SYLLABSE COVERRAGE | | Department: - Mechanical Engg. (5th Sem.) | | Subject- Machine Design | | |
|--|-------------|---|---|---|--|---------|
| | | Course- Diplor | ma | Duration -3 Years | | |
| | | Total Periods -70 | | Theory-70 | | |
| | | | | | | |
| Sr no. • | Period No's | Торіс | Details | Instruction Reference | Additional Study Recommended | Remarks |
| 1 | 1-7 | Introduction | Design – Definition, Type of design, necessity of design 1.1.1 Comparison of designed and un-designed work 1.1.2 Design procedure 1.1.3 Characteristics of a good designer 1.2 Design terminology: stress, strain, factor of safety, factors affecting factor of safety, stress concentration, methods to reduce stress concentration, fatigue, endurance limit. 1.2.1 General design consideration 1.2.2. Codes and Standards (BIS standards) 1.3 Engineering materials and their mechanical properties 1.3.1 Properties of engineering materials: elasticity, plasticity, malleability, ductility, toughness, hardness and resilience. Fatigue, creep, tenacity, strength | Machine Design by R.S. Khurmi and JK Gupta | Machine Design by V.B. Bhandari | |
| | | | 1.3.2 Selection of materials, | | | |
| 2 | 8-14 | Design Failure | criterion for material selection 2.1 Various design failure theories- maximum stress theory, maximum strain theory 2.2 Classification of loads 2.3 Design under tensile, compre- torsional loads | | do | |
| 3 | 15-24 | Design of Shafts | 3.1 Type of shafts, shaft materials, Type of loading on shafts, standard sizes of shafts available 3.2 Shafts subjected to torsion only, determination of shaft diameter (hollow and solid shaft) on the basis of Strength criterion Rigidity criterion 3.3 Determination of shaft diameter (hollow and solid shaft) subjected to bending 3.4 Determination of shaft diamet and solid shaft) subjected to combin and bending | do | do | |

chieran ~

| 4 | 25-29 | Decision (14 | | | | |
|---|-------|----------------|--|----|----|----|
| | 25-29 | Design of Keys | | | | |
| | | | keys, functions of keys | 5 | | |
| | | | 4.2 Failure of keys (by Shearing and Crushing) | | | |
| | | | | do | do | |
| | | | 4.3 Design of keys (Determination | | | |
| | | | of key dimension) | | | |
| 5 | 30-51 | Design | 4.4 Effect of keyways on shaft stren |)E | | |
| | | of Joints | Types of joints - Temporary and | | | |
| | | | permanent joints, utility of various joints | | | |
| | | | | | | |
| | | | 5.1 Temporary Joint 5.1.1 Knuckle Joints – Different | | | |
| | | | parts of the joint material | | | |
| | | | parts of the joint, material used for | | | |
| | | | the joint, type of knuckle Joint, design of the knuckle joint | | | |
| | | | 5.1.2 Cotter Joint | | | |
| | | | 5.1.2 Cotter Joint – Different parts of the spigot and socket joints, | | | |
| | | | Design of spigot and socket joints, | | | |
| | | | 5.2 Permanent Joint | | | |
| | | | 5.2.1 Welded Joint - Welding | | | |
| | | | symbols. Type of welded joint, | do | do | |
| | | <i>k</i> . | strength of parallel and transverse | | | -1 |
| | | | fillet welds | | | |
| | | | 5.2.2 Strength of combined parallel | | | |
| | | | and transverse weld | | | |
| | | | 5.2.3 Riveted Joints: Rivet | | | |
| | | | materials, Rivet heads, leak | | | |
| | | | proofing of riveted joint – caulking | | | |
| | | | and fullering | | | |
| | | | 5.2.4 Different modes of rivet joint | | | |
| | | | Tallure | | | |
| | | | 5.2.5 Design of riveted joint – Lap | | - | |
| 6 | 52.59 | | single and multi-riveted joint | | | |
| 0 | 52-58 | Design | Necessity of a coupling, advanta | | | |
| | | of Flange | coupling, types of couplings, desig | | | |
| | | Coupling | coupling, design of flange coupl | do | do | |
| 7 | 50.50 | | protected type and unprotected typ | | | |
| 7 | 59-70 | Design of | 1.1 Introduction, Advantages and | | | |
| | | Screwed | Disadvantages of screw joints | | | |
| | | Joints | location of screw joints | | | |
| | | | 7.2 Important terms used in screw | | 1 | |
| | | | threads, designation of screw | | | 1 |
| | | | threads | do | do | |
| | | | 7.3 Initial stresses due to screw up | | | |
| | | | forces, stresses due to combined | 1 | | |
| | | | forces | | | |
| | | | 7.4 Design of bolts for cylinder cover | | | |

| Approved | HOD Sign |
|----------------|----------|
| Date: 07/08/23 | cluera |
| | cevena |

.